



#### **MBF 20 - INDUSTRIAL THREE PHASE**



FOOD INDUSTR



CHEMICAL-PHARMACEUTICAL





- ✓ Side channel blower motor , powerful and silent, totally maintenance free, suitable for continuous duty
- $\checkmark$  Low noise level
- ✓ Easy filter replacement
- $\checkmark$  Reduced downtime of machine tools
- ✓ Possibility of integration on other vacuum cleaners

- ✓ Modularity is guaranteed to fulfil the client's needs
- $\checkmark\,$  Full customization for specific needs
- $\checkmark\,$  Pressure relief valve for motor protection
- ✓ Long lasting

SUCTION UNIT		
Voltage	V - Hz	400 - 50
Power	kW	1,8
Electrical protection	IP	55/F
Max water lift	mmH0O	3000
Max air flow	m³/h	270
Suction inlet	mm	50
Noise level (EN ISO 3744)	dB(A)	70
FILTER UNIT		
Filter Type		Star
Surface - Diameter	cm²-mm	8.000 - 360
Material - Efficiency	IEC 60335-2-69	Polyester - ANT M
Cleaning system		Manual
Capacity	lt	25
VOLUME		
Dimensions	cm	35x70x50h
Weight	kg	40
	www	v.mastervacuums.com



### SUCTION UNIT

The suction unit is a side channel blower, with direct coupling between the motor and the impeller fan. It designed without any transmission system, and is therefore silent, totally maintenance free and suitable for continuous duty operations.

# FILTER UNIT

The large surface star antistatic filter, located inside the filter chamber, is made of polyester and provides high resistance against clogging and passage of fine dust. It is possible to clean the filter using an integrated mechanical system: an external lever shakes the filter vertically and enables to clean the filter thoroughly and safely, maintaining constant suction performance and preventing any dispersion of dust in the environment.

#### Source Collection Unit

The unit is manufactured with thick painted steel for improved sturdiness and long-lasting lifetime

# 

- ✓ OTHER VOLTAGES AND FREQUENCIES AVAILABLE UPON REQUEST
- ✓ ABSOLUTE HEPA FILTER /H14
- ✓ STAINLESS STEEL COLLECTION TANK
- ✓ STAINLESS STEEL TANK AND FILTER CHAMBER
- ✓ ACTIVATED CARBON FILTER
- ✓ PRESSURE DIFFERENTIAL KI<mark>T FOR USE OF DISPOSABLE BAG</mark>