

) CE

#### **MBFV 20 - INDUSTRIAL THREE PHASE**





OEM ORIGINAL EQUIPMENT MANUFACTURERS





COFFEE , TEA, TOBACCO PROCESSING

- ✓ Side channel blower motor , powerful and silent, totally maintenance free, suitable for continuous duty
- $\checkmark$  Integrated filter cleaning system
- ✓ Complete steel construction
- ✓ Pressure relief valve for motor protection
- ✓ Low noise level





- ✓ Easy filter replacement
- $\checkmark$  Reduced downtime of machine tools
- ✓ Possibility of integration on other vacuum cleaners
- ✓ Modularity is guaranteed to fulfil the client's needs
- $\checkmark\,$  Full customization for specific needs

SUCTION UNIT		
Voltage	V - Hz	400 - 50
Power	kW	1,8
Electrical protection	IP	55/F
Max water lift	mmH⊡O	3000
Max air flow	m³/h	270
Suction inlet	mm	50
Noise level (EN ISO 3744)	dB(A)	69
FILTER UNIT		
Filter Type		Star
Surface - Diameter	cm²-mm	8.000 - 360
Material - Efficiency	IEC 60335-2-69	Polyester - ANT M
Cleaning system		Manual
Capacity	lt	25
VOLUME		
Dimensions	cm	54x55x103h
Weight	kg	45
www.mastervacuums.com		

www.mastervacuums.com master@mastervacuums.com



## SUCTION UNIT

The suction unit is a side channel blower, with direct coupling between the motor and the impeller fan. It designed without any transmission system, and is therefore silent, totally maintenance free and suitable for continuous duty operations.

A pressure relief valve protects the motor, providing additional air for cooling.

## FILTER UNIT

The large surface star antistatic filter, located inside the filter chamber, is made of polyester and provides high resistance against clogging and passage of fine dust.

### COLLECTION UNIT

The unit is manufactured with thick painted steel for improved sturdiness and long-lasting lifetime

# 

- ✓ ABSOLUTE HEPA FILTER /H14
- ✓ STAINLESS STEEL CHAMBER
- ✓ STAINLESS STEEL TANK AND FILTER CHAMBER
- ✓ EARTH GROUNDING
- ✓ OTHER VOLTAGES AND FREQUENCIES AVAILABLE UPON REQUEST