

) ((

245 AIR 7V - AIR POWERED





METALWORKING



- ✓ Complete steel construction
- ✓ Extractable collection container with optional use of disposable bags
- ✓ Compact and mobile
- ✓ High filtration efficiency

- ✓ Compressed air supply through a double Venturi suction unit
- $\checkmark\,$ Large surface antistatic filter
- ✓ Low noise level
- \checkmark Easy to handle

SUCTION UNIT		
Air supply	l / min	729
Air supply pressure	bar	6
Ø Air supply hose	mm	12
Max water lift	mmH⊡O	3700
Max air flow	m³/h	150
Noise level (EN ISO 3744)	dB(A)	68
FILTER UNIT		
Filter Type		Star
Surface - Diameter	cm²-mm	20.000 - 420
Material - Efficiency	IEC 60335-2-69	Polyester - ANT M
Cleaning system		Manual
Capacity	lt	45
VOLUME		
Dimensions	cm	58x63x119h
Weight	kg	46

www.mastervacuums.com master@mastervacuums.com



SUCTION UNIT

The head includes a pressure and a vacuum gauge, in order to detect the clogging of the filter

The suction is provided by a venturi compressed-air-driven suction unit, protected inside a strong steel chassis, which contains also sound absorbing material to minimize noise during service. The suction is developed by a venturi-type vented suction unit, protected inside a solid steel head, containing sound absorbing material that minimizes noise during service.



FILTER UNIT

The large surface star filter, located inside the filter chamber, is made of polyester and provides high resistance against clogging and passage of fine dust.

It is possible to clean the filter using an integrated mechanical system: an external lever shakes the filter vertically and enables to clean the filter thoroughly and safely, maintaining constant suction performance and preventing any dispersion of dust in the environment.



The detachable steel collection tank has a quick release system for the rapid disposal of the sucked material.

- ✓ ABSOLUTE HEPA FILTER /H14
- ✓ PTFE COATED FILTER CLASS M
- ✓ HEAT RESISTANT FILTER (UP TO 250° CELSIUS)
- ✓ STAINLESS STEEL COLLECTION TANK
- ✓ STAINLESS STEEL TANK AND FILTER CHAMBER
- ✓ CYCLONE FOR FILTER PROTECTION
- ✓ OTHER VOLTAGES AND FREQUENCIES AVAILABLE UPON REQUEST