

CE

STEELWORKS AND FOUNDRIES FOOD INDUSTRY

VS600 T125 - INDUSTRIAL THREE PHASE







WASTE TREATMENT - RECYCLING

- ✓ Complete steel construction
- ✓ Three powerful by pass motors with independent cooling
- ✓ Compact and mobile
- ✓ Modularity is guaranteed to fulfil the client's needs
- ✓ Very suitable for the suction of large quantities of material







- ✓ Complete, quick and safe discharge
- ✓ Pressure relief valve for motor protection
- ✓ Side channel blower motor , powerful and silent, totally maintenance free, suitable for continuous duty
- ✓ Forklift intakes as standard
- ✓ Integrated filter cleaning system

SUCTION UNIT		
Voltage	V - Hz	400 - 50
Power	kW	12,5
Max waterlift	mmH2O	4.000
Max air flow	m³/h	1.100
Suction inlet	mm	80
Noise level (EN ISO 3744)	dB(A)	75
FILTER UNIT		
Filter Type		Star
Surface - Diameter	cm²-mm	49.000
Material - Efficiency	IEC 60335-2-69	Polyester - ANT M
Air load on filter	m³/m²/h	225
-		-
Air load on filter		225
Air load on filter Cleaning system		225
Air load on filter Cleaning system		225 Manual
Air load on filter Cleaning system COLLECTION UNIT Discharge system	m³/m²/h	225 Manual Frontal discharge
Air load on filter Cleaning system COLLECTION UNIT Discharge system Capacity	m³/m²/h	225 Manual Frontal discharge
Air load on filter Cleaning system COLLECTION UNIT Discharge system Capacity VOLUME	m³/m²/h lt.	225 Manual Frontal discharge 600

www.mastervacuums.com master@mastervacuums.com



SUCTION UNIT

The suction unit is a side channel blower, with direct coupling between the motor and the impeller fan. It designed without any transmission system, and is therefore silent, totally maintenance free and suitable for continuous duty operations.

FILTER UNIT

It is possible to clean the filter using an integrated mechanical system: an external lever shakes the filter vertically and enables to clean the filter thoroughly and safely, maintaining constant suction performance and preventing any dispersion of dust in the environment.

COLLECTION UNIT

The sucked material sets down into the container equipped with castors. Thanks to the safe and complete frontal discharge it's easy to empty the container without get in contact with dirt. The industrial vacuum is mounted on a robust epoxy painted chassis, with polyurethane castors and forklift intakes.

✓ OTHER VOLTAGES AND FREQU<mark>ENCIES AVAILABLE UPON REQUEST</mark>